

# CF ... T(CF ... T-W, CF ... T-CP):

2-PIECE , SELF LUBRICATING

Dimensions in inches

WEIA Bearig Type	B +.0015 -.0005	Thread UNF-2B	D Ref	H Ref	W ±.005	A ±.015	C +.062 -.031	J ±.010	K ±.010	Ball Dia Ref	Misalign Angle ( $\alpha^\circ$ )	ULT.Radial Static Load Lbs.	Approx Brg.Wgt. Lbs.
CF3T	0.1900	10-32	0.625	0.234	0.312	1.062	0.500	0.312	0.406	0.437	10	1450	0.04
CF4T	0.2500	1/4-28	0.750	0.250	0.375	1.312	0.687	0.375	0.469	0.500	13.5	2675	0.05
CF5T	0.3125	5/16-24	0.875	0.312	0.437	1.375	0.687	0.437	0.500	0.625	11	3575	0.08
CF6T	0.3750	3/8-24	1.000	0.359	0.500	1.625	0.812	0.562	0.687	0.719	11	5325	0.13
CF7T	0.4375	7/16-20	1.125	0.406	0.562	1.812	0.937	0.625	0.750	0.812	10.5	6385	0.18
CF8T	0.5000	1/2-20	1.312	0.453	0.625	2.125	1.062	0.750	0.875	0.937	10	8550	0.29
CF10T	0.6250	5/8-18	1.500	0.484	0.750	2.500	1.375	0.875	1.000	1.125	13	9478	0.43
CF12T	0.7500	3/4-16	1.750	0.593	0.875	2.875	1.562	1.000	1.125	1.312	12	13167	0.65

