

CM(CM-W, CM-CP):

2-PIECE

Dimensions in inches

WEIYA Bearing Type	B +.0015 -.0005	Thread UNF-3A/2A	D Ref	H Ref	W ±.005	A ±.015	C +.062 -.031	Ball Dia Ref	Misalign Angle (α°)	ULT.Radial Static Load Lbs.	Approx Brg.Wgt. Lbs.
CM3	0.1900	10-32	0.625	0.234	0.312	1.250	0.750	0.437	10	2074	0.03
CM4	0.2500	1/4-28	0.750	0.250	0.375	1.562	1.000	0.500	13.5	3820	0.04
CM5	0.3125	5/16-24	0.875	0.312	0.437	1.875	1.250	0.625	11	5110	0.06
CM6	0.3750	3/8-24	1.000	0.359	0.500	1.938	1.250	0.719	11	7605	0.11
CM7	0.4375	7/16-20	1.125	0.406	0.562	2.125	1.375	0.812	10.5	9122	0.15
CM8	0.5000	1/2-20	1.312	0.453	0.625	2.438	1.500	0.937	10	12224	0.24
CM10	0.6250	5/8-18	1.500	0.484	0.750	2.625	1.625	1.125	13	13540	0.36
CM12	0.7500	3/4-16	1.750	0.593	0.875	2.875	1.750	1.312	12	18810	0.57

