

CM...T(CM...T-W, CM...T-CP): 2-PIECE , SELF LUBRICATING

Dimensions in inches

| WEIYA Bearing Type | B +.0015 -.0005 | Thread UNF-3A/2A | D Ref | H Ref | W ±.005 | A ±.015 | C +.062 -.031 | Ball Dia Ref | Misalign Angle (α°) | ULT.Radial Static Load Lbs. | Approx Brg.Wgt. Lbs. |
|--------------------|-----------------------|---------------------|----------|----------|------------|------------|---------------------|-----------------|--------------------------------------|-----------------------------|----------------------|
| CM3T | 0.1900 | 10-32 | 0.625 | 0.234 | 0.312 | 1.250 | 0.750 | 0.437 | 10 | 1450 | 0.03 |
| CM4T | 0.2500 | 1/4-28 | 0.750 | 0.250 | 0.375 | 1.562 | 1.000 | 0.500 | 13.5 | 2675 | 0.04 |
| CM5T | 0.3125 | 5/16-24 | 0.875 | 0.312 | 0.437 | 1.875 | 1.250 | 0.625 | 11 | 3575 | 0.06 |
| CM6T | 0.3750 | 3/8-24 | 1.000 | 0.359 | 0.500 | 1.938 | 1.250 | 0.719 | 11 | 5325 | 0.11 |
| CM7T | 0.4375 | 7/16-20 | 1.125 | 0.406 | 0.562 | 2.125 | 1.375 | 0.812 | 10.5 | 6385 | 0.15 |
| CM8T | 0.5000 | 1/2-20 | 1.312 | 0.453 | 0.625 | 2.438 | 1.500 | 0.937 | 10 | 8550 | 0.24 |
| CM10T | 0.6250 | 5/8-18 | 1.500 | 0.484 | 0.750 | 2.625 | 1.625 | 1.125 | 13 | 9478 | 0.36 |
| CM12T | 0.7500 | 3/4-16 | 1.750 | 0.593 | 0.875 | 2.875 | 1.750 | 1.312 | 12 | 13167 | 0.57 |

