

SCF ••• T(SECF ••• T):

2-PIECE STINLESS STEEL, SELF LUBRICATING

Dimensions in inches

WEIYA Bearing Type	B +0.0015 -0.0005	Thread UNF-2B	D Ref	H Ref	W ±.005	A ±.015	C +0.062 -0.031	J ±.010	K ±.010	Ball Dia Ref	Misalign Angle (α°)	Stat Co (Lbs)		Approx Brg.Wgt Lbs.
												SCFT	SECF	
*SCF3T	0.1900	10-32	0.625	0.234	0.312	1.062	0.500	0.312	0.406	0.437	10	930	—	0.04
*SCF4T	0.2500	1/4-28	0.750	0.250	0.375	1.312	0.687	0.375	0.469	0.500	13.5	1380	—	0.05
SCF5T	0.3125	5/16-24	0.875	0.312	0.437	1.375	0.687	0.437	0.500	0.625	11	2100	6451	0.08
SCF6T	0.3750	3/8-24	1.000	0.359	0.500	1.625	0.812	0.562	0.687	0.719	11	3080	8627	0.13
SCF7T	0.4375	7/16-20	1.125	0.406	0.562	1.812	0.937	0.625	0.750	0.812	10.5	3790	9370	0.18
SCF8T	0.5000	1/2-20	1.312	0.453	0.625	2.125	1.062	0.750	0.875	0.937	10	4720	15130	0.29
SCF10T	0.6250	5/8-18	1.500	0.484	0.750	2.500	1.375	0.875	1.000	1.125	13	5870	16922	0.43
SCF12T	0.7500	3/4-16	1.750	0.593	0.875	2.875	1.562	1.000	1.125	1.312	12	7520	25549	0.65

