

# SCM···T(SECM···T):

2-PIECE STINLESS STELL, SELF LUBRICATING

Dimensions in inches

WEYA Bearing Type	B +.0015 -.0005	Thread UNF-3A/2A	D Ref	H Ref	W ±.005	A ±.015	C +.062 -.031	Ball Dia Ref	Misalign Angle ( $\alpha^\circ$ )	Stat Co (Lbs)		Approx Brg.Wgt. Lbs.
										SCMT.	SECMT	
*SCM3T	0.1900	10-32	0.625	0.234	0.312	1.250	0.750	0.437	10	912	—	0.03
*SCM4T	0.2500	1/4-28	0.750	0.250	0.375	1.562	1.000	0.500	13.5	1370	—	0.04
SCM5T	0.3125	5/16-24	0.875	0.312	0.437	1.875	1.250	0.625	11	2050	6451	0.06
SCM6T	0.3750	3/8-24	1.000	0.359	0.500	1.938	1.250	0.719	11	3040	8627	0.11
SCM7T	0.4375	7/16-20	1.125	0.406	0.562	2.125	1.375	0.812	10.5	3780	9370	0.15
SCM8T	0.5000	1/2-20	1.312	0.453	0.625	2.438	1.500	0.937	10	4700	15130	0.24
SCM10T	0.6250	5/8-18	1.500	0.484	0.750	2.625	1.625	1.125	13	5860	16922	0.36
SCM12T	0.7500	3/4-16	1.750	0.593	0.875	2.875	1.750	1.312	12	7512	25549	0.57

